

Package: surveynnet (via r-universe)

December 10, 2024

Title Neural Network for Complex Survey Data

Version 1.0.0

Description The surveynnet package extends the functionality of nnet (Venables and Ripley, 2002), which already supports survey weights, by enabling it to handle clustered and stratified data. It achieves this by incorporating design effects through the use of effective sample sizes in the calculations, performed by the package described in Valliant et al. (2023), by following the methods outlined by Chen and Rust (2017) and Valliant et al. (2018).

License MIT + file LICENSE

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.2.3

URL <https://github.com/237triangle/surveynnet>

BugReports <https://github.com/237triangle/surveynnet/issues>

Imports dplyr, nnet, PracTools, stats, survival

Depends R (>= 2.10)

LazyData true

Config/pak/sysreqs libgdal-dev gdal-bin libgeos-dev libssl-dev
libproj-dev libsqlite3-dev libudunits2-dev

Repository <https://237triangle.r-universe.dev>

RemoteUrl <https://github.com/237triangle/surveynnet>

RemoteRef HEAD

RemoteSha 0887c4091963e278c48162ddb125e0f27df82c10

Contents

body_fat	2
nhanes.demo	2
predict.surveynnet	3
surveynnet	4

Index**6**

body_fat	<i>Simple body fat example data</i>
----------	-------------------------------------

Description

Simple body fat example data

Usage

body_fat

Format

body_fat:

A data frame with 12 rows and 9 columns:

Subject Subject ID

group group

Weight_kg weight

Height_cm height

Age age

pct_body_fat percent body fat

survey_wt survey weight

stratum stratum

cluster cluster

nhanes.demo	<i>Nhanes example</i>
-------------	-----------------------

Description

Nhanes example

Usage

nhanes.demo

Format

nhanes.demo:
 A data frame with 6230 rows and 9 columns:
SEQN Respondent sequence number
SDMVPSU Masked variance pseudo-PSU
SDMVSTRA Masked variance pseudo-stratum
WTMEC2YR Full sample 2 year MEC exam weight
BMXHT Standing height (cm)
BMXWT Weight (kg)
BMXBMI Body mass index (kg/m**2)
BPXSY1 Systolic blood pressure
BPXDI1 Diastolic blood pressure

predict.surveynnet *Predict response from fitted nnet, using new data*

Description

Predict response from fitted nnet, using new data

Usage

```
## S3 method for class 'surveynnet'
predict(object, newdat, ...)
```

Arguments

object	The surveynnet object (returned by surveynnet())
newdat	The matrix or data frame of test examples. Must be of the same structure as the data matrix used to fit the surveynnet object.
...	arguments passed to or from other methods

Value

The matrix/vector of values returned by the trained network. Note: it is possible to pass type = "raw" or type = "class" as appropriate. See predict.nnet() for more details.

Examples

```
# From the example in `surveynnet` help file:
y <- body_fat$pct_body_fat
x <- body_fat[,c("Weight_kg", "Height_cm", "Age")]
weight <- body_fat$survey_wt
strat <- body_fat$stratum
clust <- body_fat$cluster
```

```

y[strat==1] <- y[strat==1] + 30*0.00015*rnorm(sum(strat==1))
y[strat==2] <- y[strat==2] + 30*0.15*rnorm(sum(strat==2))
myout <- surveynnet(x,y,weight = weight, strat = strat, clust=clust)
newdat <- 2*x+rnorm(dim(x)[1])
predict(myout, newdat = newdat)

```

surveynnet

Neural Net for Complex Survey Data

Description

The `surveynnet` package extends the functionality of `nnet` (Venables and Ripley, 2002), which already supports survey weights, by enabling it to handle clustered and stratified data. It achieves this by incorporating design effects through the use of effective sample sizes in the calculations, performed by the package described in Valliant et al. (2023), by following the methods outlined by Chen and Rust (2017) and Valliant et al. (2018).

Usage

```
surveynnet(x, y, weight, strat, clust, comp_cases = F, ...)
```

Arguments

<code>x</code>	Matrix or data frame of predictors. Must not contain any missing values.
<code>y</code>	Vector of targets / response values. Must not contain any missing values.
<code>weight</code>	The weights for each sample.
<code>strat</code>	The stratum for each sample.
<code>clust</code>	The cluster for each sample.
<code>comp_cases</code>	If TRUE, filter out missing values from <code>x</code> , <code>y</code> , <code>weight</code> , <code>strat</code> , and <code>clust</code> . Default FALSE. Note that in either case, the dimensions of all data mentioned above must agree.
<code>...</code>	Additional arguments to be passed into <code>PracTools::deffCR</code> or <code>nnet::nnet</code> . See documentation of those packages and functions for more details. Note that for the neural net (<code>nnet</code>), the default here is set to 3 layers ("size" parameter) and maximum iterations ("maxit" parameter) is set to 2000.

Value

A list containing two objects:

- A dataframe with the fitted values of the neural nets, using: no weights ("fitted"), the user-inputted weights ("fitted_weighted"), and the new method that adjusts the weights by using a design effect incorporating cluster and strata ("fitted_deff").
- The fitted neural network object (from `nnet`), using the novel design-effect based weights; this can be used to predict the outcomes for new observations.

References

- Venables WN, Ripley BD (2002). Modern Applied Statistics with S, Fourth edition. Springer, New York. ISBN 0-387-95457-0, <https://www.stats.ox.ac.uk/pub/MASS4/>.
- Chen, S., and K. F. Rust. 2017. "An Extension of Kish's Formula for Design Effects to Two- and Three-Stage Designs with Stratification.", *Journal of Survey Statistics and Methodology*,5 (2): 111–30.
- Valliant, R., J. A. Dever, and F. Kreuter. 2018. *Practical Tools for Designing and Weighting Survey Samples* .2nd ed. New York: Springer-Verlag.
- Valliant, R., J. A. Dever, and F. Kreuter. 2023. *PracTools: Tools for Designing and Weighting Survey Samples, Version 1.4* . <https://CRAN.R-project.org/package=PracTools>

Examples

```
# short example with body fat dataset
y <- body_fat$pct_body_fat
x <- body_fat[,c("Weight_kg", "Height_cm", "Age")]
weight <- body_fat$survey_wt
strat <- body_fat$stratum
clust <- body_fat$cluster
y[strat==1] <- y[strat==1] + 30*0.00015*rnorm(sum(strat==1))
y[strat==2] <- y[strat==2] + 30*0.15*rnorm(sum(strat==2))
myout <- surveynnet(x,y,weight = weight, strat = strat, clust=clust)
myout

# NHANES example
# Predicting Diastolic BP from BMI, Systolic BP and Height
# PLEASE NOTE: for this example, pass "nest=TRUE" into the
# "..." parameters of the main function `surveynnet`

x <- nhanes.demo[,c("BMXBMI", "BPXSY1", "BMXHT")]
weight <- nhanes.demo$WTMEC2YR
strat <- nhanes.demo$SDMVSTRA
clust <- nhanes.demo$SDMVPSU
y <- nhanes.demo$BPXDI1
myout <- surveynnet(x,y,weight = weight, strat = strat, clust=clust, nest=TRUE)
head(myout$results, 15)
```

Index

* **datasets**

body_fat, [2](#)

nhanes.demo, [2](#)

body_fat, [2](#)

nhanes.demo, [2](#)

predict.surveynnet, [3](#)

surveynnet, [4](#)